



| Model | GPS-640U | GPS-641U | GPS-642U |
|---|-------------------|-------------------|-------------------|
| Operation Voltage Range | 90 – 264Vac | 90 – 264Vac | 90 – 264Vac |
| Operation Frequency Range | 45 – 65HZ | 45 – 65HZ | 45 – 65HZ |
| Output Voltage Range | 0 – 16V | 0 – 32V | 0 – 60V |
| Output Current Range | 0 – 40A | 0 – 20A | 0 – 11A |
| Power Factor | ≥97% | ≥97% | ≥97% |
| Efficiency (230V/100V) | ≥86% / 83% | ≥88% / 85% | ≥89% / 86% |
| Full Load Input Current(230V/100V) | ≤ 3.35A/8.0A | ≤3.3A /8.0A | ≤3.35A/8.0A |
| No Load Input Current(230V) | ≤ 200mA | ≤ 200mA | ≤ 200mA |
| Volt Meter Accuracy (0-9.9V) | ≤ 0.2% + 4 digits | ≤ 0.2% + 4 digits | ≤ 0.2% + 4 digits |
| Volt Meter Accuracy(≥10V) | ≤ 0.2% + 1 digit | ≤ 0.2% + 2 digits | ≤ 0.2% + 2 digits |
| Current Meter Accuracy(0-9.9A) | ≤ 0.3% + 4 digits | ≤ 0.3% + 4 digits | ≤ 0.3% + 4 digits |
| Current Meter Accuracy(≥10A) | ≤ 0.3% + 2 digits | ≤ 0.3% + 2 digit | ≤ 0.3% + 1 digit |
| Constant Voltage | | | |
| Load Regulation (0-100%) | ≤ 20mV | ≤ 20mV | ≤ 20mV |
| Line Regulation (170 -264V) | ≤ 5mV | ≤ 5mV | ≤ 5mV |
| Ripple & Noise (Peak-Peak) | ≤ 35mV | ≤ 30mV | ≤ 30mV |
| Ripple & Noise (r.m.s) | ≤ 5mV | ≤ 5mV | ≤ 5mV |
| Set Accuracy | ≤ 0.2% + 50mV | ≤ 0.2% + 0.1V | ≤ 0.2% + 0.1V |
| Transient Response Time (50%-100%) | ≤ 1.0ms | ≤ 1.0ms | ≤ 1.0ms |
| Constant Current | | | |
| Load Regulation (90%-10% Rated Voltage) | ≤ 150mA | ≤ 100mA | ≤ 100mA |
| Line Regulation (170-264V) | ≤ 30mA | ≤ 20mA | ≤ 20mA |
| Ripple & Noise (Peak-Peak) | ≤ 200mA | ≤ 100mA | ≤ 100mA |
| Set Accuracy | ≤ 0.2% + 0.2A | ≤ 0.2% + 0.1A | ≤ 0.2% + 0.1A |
| Size (L×W×H mm) | 248×188×81 | 248×188×81 | 248×188×81 |